


Product data sheet

Specifications



Starter, Definite Purpose,
nonreversing, 40A, 3 pole, 3 phase,
120 VAC coil, melting alloy overload,
open style

8911DPSO43V02

Product availability : Stock - Normally stocked in distribution facility

Price* : 431.55 USD

Main

Product	Definite Purpose Starter
Ampere Rating	40 A
Horsepower Rating	3 hp 115 V AC, 1 phase 10 hp 230 V AC, 3 phase 7.5 hp 230 V AC, 1 phase 20 hp 460 V AC, 3 phase 25 hp 575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Phase	3 phase

Complementary

Enclosure Rating	Not rated (open device)
Locked Rotor Amperes	240 A 230 V AC 200 A 460 V AC 160 A 575 V AC
Number of Poles	3P
Range	DPS
Overload Type	Melting alloy
Number of Thermal Units	3

Ordering and shipping details

Category	21381-8911 DP
Discount Schedule	CP1
GTIN	785901856368
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	5.10 in (12.954 cm)
Package 1 Width	4.90 in (12.446 cm)
Package 1 Length	7.90 in (20.066 cm)
Package 1 Weight	2.31 lb(US) (1.048 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)