

Product availability : Non-Stock - Not normally stocked in distribution facility



Price** : 200.00 USD



Main

Device short name	G
Enclosure type	Standard environment enclosure indoor
Factory modification	2-way pressure release valve
Product specific application	Control electrically driven water pumps and air compressors
Range of product	Square D Pumptrol
Switch application	Standard

Complementary

Adjustable range on rising pressure	448.16...1378.95 kPa (65...200 psi)
Approximate adjustable differential	137.90...275.79 kPa (20...40 psi)
Depth	93.47 mm (3.68 in)
Electrical connection	Screw clamp terminal
Fixing mode	By brackets
Fluid connection type	0.25 inch NPSF internal
Height	145.29 mm (5.72 in)
Material	Zinc plated steel flange
Materials in contact with fluid	Nitrile (Buna-N) diaphragm
Maximum pressure	300 psig
Maximum Horse Power Rating	2 hp 115 V AC, 1 phase 3 hp 115 V AC, 3 phase 3 hp 230 V AC, 1 phase 5 hp 230 V AC, 3 phase 5 hp 460/575 V AC, 1 phase 5 hp 460/575 V AC, 3 phase
Number of poles	2
Permissible voltage	575 V AC
Pressure actuator	Diaphragm
Pressure setting range	551.58...689.48 kPa (80...100 psi)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net weight	1.02 kg (2.25 lb(US))
Range on decreasing pressure	275.79...1172.11 kPa (40...170 psi)
Switch function	DPST
Width	87.38 mm (3.44 in)

Environment

NEMA degree of protection	NEMA 1
Product certifications	CSA file LR25490 UL listed file E12158 CCN NKPZ

Ordering and shipping details

Category	21536 - 9013 G COMMERCIAL PRESSURE SWITCH
Discount Schedule	CP7G
GTIN	00785901560074
Package weight(Lbs)	1.02 kg (2.25 lb(US))
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------