

Product data sheet

Characteristics

9070T100D20

XFMR CONTROL 100VA 208/230/460V-115V

Product availability : Stock - Normally stocked in distribution facility



Price** : 207.00 USD



Main

Product or component type	Industrial Control Transformer
Power Rating	100 VA
Primary Voltage	208/230/460 V
Secondary Voltage	115 V
Type	T

Complementary

Number of Phases	1 phase
Power Rating	100 VA
Primary to Secondary Voltage	208/230/460 V 115 V
Temperature rise	55 °C
Electrical connection	Screw clamp terminals
Height	81.28 mm (3.2 in)
Width	95.25 mm (3.75 in)
Depth	91.19 mm (3.59 in)
Material	Copper winding
Fingersafe Cover Compatibility	FSC1

Environment

Product certifications	CSA file LR37055 guide 184-N-90 CE UL listed file E61239
Enclosure Type	Not rated (open device)
Insulation temperature	221 °F (105 °C)

Ordering and shipping details

Category	16200 - 9070 T (NOT TF) 50-200VA
----------	----------------------------------

Discount Schedule	CP8
GTIN	00785901905059
Package weight(Lbs)	2.47 kg (5.45 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	10 Years
----------	----------