

FA34030

FA/LA MOLDED CASE CIRCUIT BREAKER, 480V 30A, 3P

Product availability : Non-Stock - Not normally stocked in distribution facility



Price** : 999.60 USD



Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip Unit Type	Thermal-magnetic
Rating Code	A

Complementary

Line Rated Current	30 A
Number of Poles	3P
Interrupt Rating	10 kA 250 V DC 25 kA 240 V AC 18 kA 480 V AC
[Ue] rated operational voltage	250 V DC 480 V AC
Mounting mode	I-Line
Electrical connection	Lugs load I-Line connection line
Wire Gauge	AWG 14...AWG 4 copper)1 AWG 12...AWG 4 aluminium)1
Terminal Type	AL50FA
Magnetic hold current	275 A
Magnetic tripping current	600 A
Phase connection	ABC
Height	162.56 mm (6.4 in)
Width	114.30 mm (4.5 in)
Depth	104.90 mm (4.13 in)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Product certifications	UL listed CSA
------------------------	------------------

Ordering and shipping details

Category	01005 - FA 480V BREAKER & SWITCH
Discount Schedule	DE2
GTIN	00785901422624
Package weight(Lbs)	2.81 kg (6.2 lb(US))
Returnability	No
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

FA34030 is replaced by:



I-Line BDA36030

PowerPact B Circuit Breaker, 30A, 3P, 600Y/347V AC, 14kA at 600Y/347 UL, I-Line

Qty 1

Reason for Substitution: End of life | Substitution date: 13 June 2019