Product data sheet Characteristics

QOB110VH5237 Mini CB, QO, 10 A, 1P, 120/240 V, 22 kA, Bolt on

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 86.00 USD



Main

Mani		
Product	Miniature circuit-breaker	
Range	QO	
Line Rated Current	10 A	
System Voltage	120 V AC 120/240 V AC	
Mounting Type	Bolt-on	
Number of Poles	1P	
Circuit Breaker Type	Standard	
Ratings	HACR rated	
Electrical Connection	Ring tongue	
3	· · · · · · · · · · · · · · · · · · ·	-

Complementary

Main		
Product	Miniature circuit-breaker	
Range	QO	
Line Rated Current	10 A	
System Voltage	120 V AC 120/240 V AC	
Mounting Type	Bolt-on	
Number of Poles	1P	
Circuit Breaker Type	Standard	
Deffere	HACR rated	
Ratings		
Ratings Electrical Connection Complementary	Ring tongue	
	Ring tongue 22 kA at: 120/240 V AC 50/60 Hz 22 kA at: 120 V AC 50/60 Hz	
Electrical Connection Complementary Inturrupt Rating	22 kA at: 120/240 V AC 50/60 Hz	
Complementary Inturrupt Rating Number of Panel Spaces	22 kA at: 120/240 V AC 50/60 Hz 22 kA at: 120 V AC 50/60 Hz	
Complementary Inturrupt Rating Number of Panel Spaces Wire Size	22 kA at: 120/240 V AC 50/60 Hz 22 kA at: 120 V AC 50/60 Hz 1	
Complementary Inturrupt Rating Number of Panel Spaces Wire Size Height	22 kA at: 120/240 V AC 50/60 Hz 22 kA at: 120 V AC 50/60 Hz 1 AWG 14AWG 8 (copper)	
Complementary Inturrupt Rating Number of Panel Spaces Wire Size Height Depth	22 kA at: 120/240 V AC 50/60 Hz 22 kA at: 120 V AC 50/60 Hz 1 AWG 14AWG 8 (copper) 3 in	
Complementary Inturrupt Rating Number of Panel Spaces Wire Size Height Depth Width	22 kA at: 120/240 V AC 50/60 Hz 22 kA at: 120 V AC 50/60 Hz 1 AWG 14AWG 8 (copper) 3 in 2.91 in	
Electrical Connection Complementary Inturrupt Rating Number of Panel Spaces Wire Size Height Depth Width Environment	22 kA at: 120/240 V AC 50/60 Hz 22 kA at: 120 V AC 50/60 Hz 1 AWG 14AWG 8 (copper) 3 in 2.91 in	
Electrical Connection Complementary	22 kA at: 120/240 V AC 50/60 Hz 22 kA at: 120 V AC 50/60 Hz 1 AWG 14AWG 8 (copper) 3 in 2.91 in 0.75 in	
Electrical Connection Complementary Inturrupt Rating Number of Panel Spaces Wire Size Height Depth Width Environment Certifications	22 kA at: 120/240 V AC 50/60 Hz 22 kA at: 120 V AC 50/60 Hz 1 AWG 14AWG 8 (copper) 3 in 2.91 in 0.75 in CSA UL listed 104 °F (40 °C)	

Environment

Certifications	CSA	
	UL listed	,
Ambient Rating	104 °F (40 °C)	1

Ordering and shipping details

Category	00015 - QOB CIRCUIT BREAKERS

Discount Schedule	DE2	
GTIN	00785901187738	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.320000000000001	
Returnability	N	
Country of origin	MX	

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2014
	Will be compliant on 3Q2014

Contractual warranty

Warranty period	18 months