

PRODUCT-DETAILS

B14-516

NON-INS RING TERM, 18-14, 5/16, MET



General Information

Extended Product Type	B14-516
Product ID	7TAI029590R0019
EAN	0786210803388
Catalog Description	NON-INS RING TERM, 18-14, 5/16, MET
Long Description	Non-Insulated Ring Terminal, Length .93 Inches, Width .50 Inches, Bolt Hole 5/16 Inch, Wire Range #18-#14 AWG, Copper, Tin Plated

Ordering

EAN	0786210803388
-----	---------------

Dimensions

Product Net Weight	.003 lb 1.361 g
--------------------	--------------------

Container Information

Package Level 1 Units	100 piece
Package Level 1 Width	1.63 in 41 mm
Package Level 1 Height	3.5 in 89 mm

Package Level 1 Depth / Length	2.63 in 67 mm
Package Level 2 Units	500 piece
Package Level 2 Width	8.9 in 226 mm
Package Level 2 Height	7 in 178 mm
Package Level 2 Depth / Length	10.7 in 272 mm
Package Level 3 Units	5000 piece
Package Level 3 Width	8.8 in 224 mm
Package Level 3 Height	6.6 in 168 mm
Package Level 3 Depth / Length	10.3 in 262 mm

Additional Information

Brand / Label	Sta-Kon
Color	Metallic
Material	Copper
Number of Batteries	0
Product Name	ELECTRICAL TERMINAL
Product Type	Non-Insulated Ring Terminal
Special Functions	These non-insulated ring terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire). Serrated barrel increases grip on wire.
Standards	UL E9809
UPC	786210803388
Voltage Rating	600 V
Wire Size	18-14 AWG

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	B14-516
Instructions and Manuals	B14-516

Classifications

ETIM 6	EC001052 - Solderless copper terminals for copper conductors
ETIM 7	EC001052 - Solderless copper terminals for copper conductors
UNSPSC	39121432
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4603 >> Electrical terminals

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

