

PRODUCT-DETAILS

BC14-10

NONINS RING TERM, HD 16-14, No10, M



General Information

Extended Product Type	BC14-10
Product ID	7TAI029590R0022
EAN	0786210801292
Catalog Description	NONINS RING TERM, HD 16-14, No10, M
Long Description	Non-Insulated Heavy Duty Ring Terminal, Length .87 Inches, Width .39 Inches, Bolt Hole #10, Wire Range #16-#14 AWG Heavy Duty, Copper, Tin Plated

Ordering

EAN	0786210801292
-----	---------------

Dimensions

Product Net Weight	.01 lb 4.535 g
--------------------	-------------------

Container Information

Package Level 1 Units	50 piece
Package Level 1 Width	1.1 in 28 mm
Package Level 1 Height	2.9 in 74 mm

Package Level 1 Depth / Length	2.09 in 53 mm
Package Level 2 Units	250 piece
Package Level 2 Width	9.4 in 239 mm
Package Level 2 Height	8.7 in 221 mm
Package Level 2 Depth / Length	15 in 381 mm
Package Level 3 Units	2500 piece
Package Level 3 Width	7.3 in 185 mm
Package Level 3 Height	8.89 in 226 mm
Package Level 3 Depth / Length	10.6 in 269 mm

Additional Information

Brand / Label	Sta-Kon
Color	Metallic
Material	Copper
Number of Batteries	0
Product Name	STA-KON AND CATAMOUNT TERMINAL
Product Type	Non-Insulated Heavy-Duty Ring Terminal
Special Functions	These non-insulated ring terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire). Serrated barrel increases grip on wire.
Standards	UL E9809
UPC	786210801292
Voltage Rating	600 V
Wire Size	16-14 AWG

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	BC14-10
Instructions and Manuals	BC14-10

Classifications

ETIM 6	EC001052 - Solderless copper terminals for copper conductors
ETIM 7	EC001052 - Solderless copper terminals for copper conductors
UNSPSC	39121432
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4603 >> Electrical terminals

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

