

PRODUCT-DETAILS

# C10-10F

## UNINS FORK TERM 12-10 No10 META



### General Information

Extended Product Type	C10-10F
Product ID	7TAI029580R0015
EAN	5414363148838
Catalog Description	UNINS FORK TERM 12-10 No10 META
Long Description	Non-Insulated Fork Terminal, Length .82 Inches, Width .38 Inches, Bolt Hole #10, Wire Range #12-#10 AWG, Copper, Tin Plated

### Ordering

EAN	5414363148838
-----	---------------

### Dimensions

Product Net Weight	.005 lb 2.268 g
--------------------	--------------------

### Container Information

Package Level 1 Units	50 piece
Package Level 1 Width	1.63 in 41 mm
Package Level 1 Height	3.5 in 89 mm

Package Level 1 Depth / Length	2.63 in 67 mm
Package Level 2 Units	250 piece
Package Level 2 Width	9.4 in 239 mm
Package Level 2 Height	8.9 in 226 mm
Package Level 2 Depth / Length	14.9 in 378 mm
Package Level 3 Units	2500 piece
Package Level 3 Width	7.1 in 180 mm
Package Level 3 Height	8.8 in 224 mm
Package Level 3 Depth / Length	10.3 in 262 mm

### Additional Information

Brand / Label	Sta-Kon
Color	Metallic
Material	Copper
Number of Batteries	0
Product Name	STA-KON AND CATAMOUNT TERMINAL
Product Type	Non-Insulated Fork Terminal
Special Functions	These non-insulated fork terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire). Serrated barrel increases grip on wire.
Standards	UL E9809
UPC	786210803487
Voltage Rating	600 V
Wire Size	12-10 AWG

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	C10-10F
Instructions and Manuals	C10-10F

### Classifications

ETIM 6	EC001052 - Solderless copper terminals for copper conductors
ETIM 7	EC001052 - Solderless copper terminals for copper conductors
UNSPSC	39121432
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4603 >> Electrical terminals

### Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

