

PRODUCT-DETAILS

C10-12

NON-INS RING TERM 12-10 1/2 META



General Information

Extended Product Type	C10-12
Product ID	7TAI029580R0016
EAN	5414363934998
Catalog Description	NON-INS RING TERM 12-10 1/2 META
Long Description	Non-Insulated Ring Terminal, Length 1.21 Inches, Width .72 Inches, Bolt Hole 1/2 Inch, Wire Range #12-#10 AWG, Copper, Tin Plated

Ordering

EAN	5414363934998
-----	---------------

Dimensions

Product Net Weight	.006 lb 2.721 g
--------------------	--------------------

Container Information

Package Level 1 Units	50 piece
Package Level 1 Width	1.63 in 41 mm
Package Level 1 Height	3.5 in 89 mm

Package Level 1 Depth / Length	2.63 in 67 mm
Package Level 2 Units	250 piece
Package Level 2 Width	8.9 in 226 mm
Package Level 2 Height	7 in 178 mm
Package Level 2 Depth / Length	10.7 in 272 mm
Package Level 3 Units	2500 piece
Package Level 3 Width	8.5 in 216 mm
Package Level 3 Height	6.6 in 168 mm
Package Level 3 Depth / Length	10.3 in 262 mm

Additional Information

Brand / Label	Sta-Kon
Color	Metallic
Material	Copper
Number of Batteries	0
Product Name	STA-KON AND CATAMOUNT TERMINAL
Product Type	Non-Insulated Ring Terminal
Special Functions	These non-insulated ring terminals are made of electrolytic copper for high conductivity. They can be installed with crimping tools having a single indenter or double indenter (recommended for solid wire). Serrated barrel increases grip on wire.
Standards	UL E9809
UPC	786210878416
Voltage Rating	600 V
Wire Size	12-10 AWG

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	C10-12
Instructions and Manuals	C10-12

Classifications

ETIM 6	EC001052 - Solderless copper terminals for copper conductors
ETIM 7	EC001052 - Solderless copper terminals for copper conductors
UNSPSC	39121432
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4603 >> Electrical terminals

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

