

PRODUCT-DETAILS

LT975-SC 3/4 90 DEG SC LT CONN



Container Information		
Package Level 1 Units	10 piece	
Package Level 1 Width	5.3 in 135 mm	
Package Level 1 Height	4.4 in 112 mm	
Package Level 1 Depth /	8.1 in	

Length	206 mm
Package Level 2 Units	50 piece
Package Level 2 Width	8.7 in 221 mm
Package Level 2 Height	4.2 in 107 mm
Package Level 2 Depth / Length	21.6 in 549 mm

Additional Information	
Application	Typical Applications Include Motor and Control, Heating and Air Conditioning, Outdoor Lighting and Transformer Connection
Brand / Label	Steel City
Color	Metallic
Material	Malleable Iron
Number of Batteries	0
Product Name	MALLEABLE IRON FITTING FOR CONDUIT
Product Type	Connectors-90 Degree
Size	3/4 Inch
Special Functions	Screw in Ferrule and Split Sealing Ring Makes for a Quick Install While Still Providing a Liquidtight Seal that Meets UL Standards
Standards	UL E23018
UPC	785991085709

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	LT975-SC	
Instructions and Manuals	LT975-SC	

Classifications		
ETIM 6	EC001180 - Screw connection for protective metallic hose	
ETIM 7	EC001180 - Screw connection for protective metallic hose	
UNSPSC	39121420	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors	

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Cable\ Protection,\ Explosion\ Proof\ and\ Lighting \rightarrow Liquid tight\ Fittings$

LT975-SC 3

