

Thermostats



GENERAL PURPOSE LIMITS L & LD SERIES

- Open on Rise
- Close when Temperature Differential is Reached
- 1/4" Quick Disconnect Terminals

"L" Series , Single Pole - Single Throw

PART NO.	°DIFF.	OPEN (°F)	CLOSE (°F)
L120	10	120	110
L125	10	125	115
L130	15	130	115
L135	15	135	120
L140	20	140	120
L145	20	145	125
L150	20	150	130
L155	20	155	135
L160	20	160	140
L165	20	165	145
L170	20	170	150
L175	20	175	155
L180-20	20	180	160
L180-40	40	180	140

PART NO.	°DIFF.	OPEN (°F)	CLOSE (°F)
L190	40	190	150
L200	40	200	160
L205	40	205	165
L225	40	225	185
L240	40	240	200
L250	40	250	210
L260	40	260	220
L270	40	270	230
L290	40	290	250
L300	40	300	260
L320	40	320	280
L340	40	340	300



Use 60T Electrical Ratings on page

"LD" Series, Single Pole - Double Pole

PART NO.	DESCRIPTION	OPEN (°F)	CLOSE (°F)	DIFFERENTIAL
LD120	SPDT Thermostats	120	105	15
LD130	SPDT Thermostats	130	115	15
LD135	SPDT Thermostats	135	120	15
LD140	SPDT Thermostats	140	120	20
LD145	SPDT Thermostats	145	125	20
LD155	SPDT Thermostats	155	135	20
LD170	SPDT Thermostats	170	150	20
LD200	SPDT Thermostats	200	160	40
LD225	SPDT Thermostats	225	185	40
LD240	SPDT Thermostats	240	200	40
LD270	SPDT Thermostats	270	230	40

Use 60T Electrical Ratings on page



H
V
A
C

ADJUSTABLE AT SERIES

- Series Covers Almost 95% of Heater and Dryer Applications
- Dial Knob
- 40° Adjustable Range
- 1/4" Quick Connect Terminals
- Use 60T Electrical Ratings

Adjustable Thermostats

PART NO.	STANDARD MOUNT	ADJUSTABLE RANGE (°F)	DIFFERENTIAL
AT012		135 175	20
AT013		175 215	40
AT014		210 250	40
AT015		250 290	40

Open on Temperature Rise

Adjustable Airflow Thermostats

PART NO.	STANDARD MOUNT	ADJUSTABLE RANGE (°F)	DIFFERENTIAL
AT021		90 130	20
AT022		140 180	20

Close on Temperature Rise

