

PRODUCT-DETAILS

5235

1.25 IN NON-INSUL LIQ-TIGHT CONN ST



General Information

Extended Product Type	5235
Product ID	7TAD01216OR0000
EAN	5414363142744
Catalog Description	1.25 IN NON-INSUL LIQ-TIGHT CONN ST
Long Description	Liquidtight Conduit Fitting, Straight, Steel, 1-1/4 Inch, Non-Insulated Steel

Ordering

EAN	5414363142744
-----	---------------

Dimensions

Product Net Weight	.6 lb 272.109 g
--------------------	--------------------

Container Information

Package Level 1 Units	5 piece
Package Level 1 Width	4.5 in 114 mm
Package Level 1 Height	4.19 in 106 mm
Package Level 1 Depth /	6 in

Length	152 mm
Package Level 2 Units	25 piece
Package Level 2 Width	4.81 in 122 mm
Package Level 2 Height	6.31 in 160 mm
Package Level 2 Depth / Length	21.44 in 545 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Steel
Number of Batteries	0
Product Name	STEEL FITTING FOR CONDUIT
Product Type	Connectors-Straight
Size	1-1/4 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210052359

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5235

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

