

PRODUCT-DETAILS

5236

1 1/2 IN NONINSUL LIQ-TIGHT CONN ST



General Information

Extended Product Type	5236
Product ID	7TAD012150R0000
EAN	5414363142768
Catalog Description	1 1/2 IN NONINSUL LIQ-TIGHT CONN ST
Long Description	Liquidtight Conduit Fitting, Straight 1-1/2 Inch, Non-Insulated Malleable Iron

Ordering

EAN	5414363142768
-----	---------------

Dimensions

Product Net Weight	.965 lb 437.642 g
--------------------	----------------------

Container Information

Package Level 1 Units	2 piece
Package Level 1 Width	4.5 in 114 mm
Package Level 1 Height	3 in 76 mm
Package Level 1 Depth /	5 in

Length	127 mm
Package Level 2 Units	10 piece
Package Level 2 Width	6.12 in 155 mm
Package Level 2 Height	6.62 in 168 mm
Package Level 2 Depth / Length	21.62 in 549 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Steel
Number of Batteries	0
Product Name	STEEL FITTING FOR CONDUIT
Product Type	Connectors-Straight
Size	1-1/2 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210052366

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5236

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

