

PRODUCT-DETAILS

5237

2 INCH NON-INSUL LIQ-TIGHT CONN ST



General Information

Extended Product Type	5237
Product ID	7TAD012150R0001
EAN	5414363142782
Catalog Description	2 INCH NON-INSUL LIQ-TIGHT CONN ST
Long Description	Liquidtight Conduit Fitting, Straight 2 Inch, Non-Insulated Malleable Iron

Ordering

EAN	5414363142782
-----	---------------

Dimensions

Product Net Weight	1.52 lb 689.342 g
--------------------	----------------------

Container Information

Package Level 2 Units	5 piece
Package Level 2 Width	6.7 in 170 mm
Package Level 2 Height	3.8 in 97 mm
Package Level 2 Depth /	9.9 in

Length 251 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Steel
Number of Batteries	0
Product Name	STEEL FITTING FOR CONDUIT
Product Type	Connectors-Straight
Size	2 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210052373

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5237

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

