
PRODUCT-DETAILS

5253

3/4 NON-INSUL 90 DEG LT CONN



General Information

Extended Product Type	5253
Product ID	7TAD012130R0002
EAN	5414363075493
Catalog Description	3/4 NON-INSUL 90 DEG LT CONN
Long Description	Liquidtight Conduit Fitting, 90 Degree 3/4 Inch, Non-Insulated Malleable Iron

Ordering

EAN	5414363075493
-----	---------------

Dimensions

Product Net Weight	.375 lb 170.068 g
--------------------	----------------------

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	4 in 102 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth /	6 in

Length	152 mm
Package Level 2 Units	50 piece
Package Level 2 Width	5.1 in 130 mm
Package Level 2 Height	6.6 in 168 mm
Package Level 2 Depth / Length	21.4 in 544 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	TUBE OR PIPE FITTING IRON OR STEEL
Product Type	Connectors-90 Degree
Size	3/4 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210052533

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5253

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

