

PRODUCT-DETAILS

5255

1-1/4 INCH NON-INSUL 90 DEG LT CONN



General Information

Extended Product Type	5255
Product ID	7TAD012170R0003
EAN	5414363142904
Catalog Description	1-1/4 INCH NON-INSUL 90 DEG LT CONN
Long Description	Liquidtight Conduit Fitting, 90 Degree 1-1/4 Inch, Non-Insulated Malleable Iron

Ordering

EAN	5414363142904
-----	---------------

Dimensions

Product Net Weight	1.13 lb 512.472 g
--------------------	----------------------

Container Information

Package Level 1 Units	5 piece
Package Level 1 Width	6.5 in 165 mm
Package Level 1 Height	4.5 in 114 mm
Package Level 1 Depth /	9.5 in

Length	241 mm
Package Level 2 Units	25 piece
Package Level 2 Width	6.81 in 173 mm
Package Level 2 Height	9.81 in 249 mm
Package Level 2 Depth / Length	23.94 in 608 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	MI FITTING FOR CONDUIT
Product Type	Connectors-90 Degree
Size	1-1/4 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210052557

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Instructions and Manuals	5255

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

