

PRODUCT-DETAILS

5332SST6

1/2 STRAIGHT 316 SS LT FITTING



General Information

Extended Product Type	5332SST6
Product ID	7TAD012380R0008
EAN	5415022449822
Catalog Description	1/2 STRAIGHT 316 SS LT FITTING
Long Description	1/2 Inch Liquidtight Fitting for Flexible Metallic Conduit, Straight, UL/CSA Listed, High UV Resistance, NEMA Ratings: 3, 3R, 4, 4X, Length 1.74 Inches/44.20mm, Width 1.33 Inches/33.78mm, Temperature Range 0 to 105 Degrees C, 316 Stainless Steel with Duraplated Ground Cone

Ordering

EAN	5415022449822
-----	---------------

Dimensions

Product Net Weight	.19 lb
	86.168 g

Container Information

Package Level 1 Units	25 piece
Package Level 1 Width	4.5 in
	114 mm

Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	6 in 152 mm
Package Level 2 Units	100 piece
Package Level 2 Width	8.62 in 219 mm
Package Level 2 Height	6.37 in 162 mm
Package Level 2 Depth / Length	9.5 in 241 mm

Additional Information

Application	Connects Flexible Metallic Liquidtight Conduit to a Box or Enclosure
Brand / Label	T&B Liquidtight Fittings
Color	Metallic
Insulation Material	Y
Material	316 Stainless Steel with Duraplated Ground Cone
Number of Batteries	0
Product Name	SS FITTING FOR CONDUIT
Product Type	Straight Fitting for Flexible Metallic Conduit
Size	1/2 Inch
Special Functions	Stronger and More UV-resistant than Nonmetallic Fittings
Standards	UL E23018, CSA
Surface Finishing	None
Temperature Range	105 °C
UPC	786210079981

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000126
Declaration of Conformity - CE	9AKK107492A9904
Instructions and Manuals	5332SST6

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

