

PRODUCT-DETAILS

# 5333SST6

## 3/4 STRAIGHT 316 SS LT FITTING



### General Information

Extended Product Type	5333SST6
Product ID	7TAD012380R0009
EAN	5415022433296
Catalog Description	3/4 STRAIGHT 316 SS LT FITTING
Long Description	3/4 Inch Liquidtight Fitting for Flexible Metallic Conduit, Straight, UL/CSA Listed, High UV Resistance, NEMA Ratings: 3, 3R, 4, 4X, Length 1.75 Inches/44.45mm, Width 1.64 Inches/41.66mm, Temperature Range 0 to 105 Degrees C, 316 Stainless Steel with Duraplated Ground Cone

### Ordering

EAN	5415022433296
-----	---------------

### Dimensions

Product Net Weight	.26 lb 117.914 g
--------------------	---------------------

### Container Information

Package Level 1 Units	25 piece
Package Level 1 Width	5 in 127 mm

Package Level 1 Height	4 in 102 mm
Package Level 1 Depth / Length	8 in 203 mm
Package Level 2 Units	50 piece
Package Level 2 Width	5.18 in 132 mm
Package Level 2 Height	8.12 in 206 mm
Package Level 2 Depth / Length	8.43 in 214 mm

### Additional Information

Application	Connects Flexible Metallic Liquidtight Conduit to a Box or Enclosure
Brand / Label	T&B Liquidtight Fittings
Color	Metallic
Insulation Material	Y
Material	316 Stainless Steel with Duraplated Ground Cone
Number of Batteries	0
Product Name	SS FITTING FOR CONDUIT
Product Type	Straight Fitting for Flexible Metallic Conduit
Size	3/4 Inch
Special Functions	Stronger and More UV-resistant than Nonmetallic Fittings
Standards	UL E23018, CSA
Surface Finishing	None
Temperature Range	105 °C
UPC	786210080000

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000126
Declaration of Conformity - CE	9AKK107492A9904
Instructions and Manuals	5333SST6

### Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

