
PRODUCT-DETAILS

5336

1.5 INCH INSUL. LIQ.TIGHT CONN ST



General Information

Extended Product Type	5336
Product ID	7TAD012160R0003
EAN	5414363075677
Catalog Description	1.5 INCH INSUL. LIQ.TIGHT CONN ST
Long Description	1-1/2 Inch Straight Malleable Iron Insulated Liquidtight Connector

Ordering

EAN	5414363075677
-----	---------------

Dimensions

Product Net Weight	.93 lb
	421.769 g

Container Information

Package Level 1 Units	2 piece
Package Level 1 Width	4.5 in
	114 mm
Package Level 1 Height	3 in
	76 mm
Package Level 1 Depth /	5 in

Length	127 mm
Package Level 2 Units	10 piece
Package Level 2 Width	6.12 in 155 mm
Package Level 2 Height	6.62 in 168 mm
Package Level 2 Depth / Length	21.62 in 549 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	INSULATED CONDUIT FTG, THREADED
Product Type	Connectors-Straight
Size	1-1/2 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210053363

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Declaration of Conformity - CE	9AKK107492A9884
Instructions and Manuals	5336

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

