

PRODUCT-DETAILS

5337

2 IN INSUL. LIQ.TIGHT CONN STRAIGHT



General Information

Extended Product Type	5337
Product ID	7TAD012150R0002
EAN	5414363075684
Catalog Description	2 IN INSUL. LIQ.TIGHT CONN STRAIGHT
Long Description	2 Inch Straight Malleable Iron Insulated Liquidtight Connector

Ordering

EAN	5414363075684
-----	---------------

Dimensions

Product Net Weight	1.375 lb 623.583 g
--------------------	-----------------------

Container Information

Package Level 2 Units	5 piece
Package Level 2 Width	6.5 in 165 mm
Package Level 2 Height	3.75 in 95 mm
Package Level 2 Depth /	9.75 in

Length 248 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	T&B LIQUIDTIGHT FITTINGS
Product Type	Connectors-Straight
Size	2 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210053370

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Declaration of Conformity - CE	9AKK107492A9884
Instructions and Manuals	5337

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

