

PRODUCT-DETAILS

5342

1/2 IN INSUL 45 DEG LIQ TIGHT CON



General Information

Extended Product Type	5342
Product ID	7TAD012130R0004
EAN	5414363075714
Catalog Description	1/2 IN INSUL 45 DEG LIQ TIGHT CON
Long Description	1/2 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

Ordering

EAN	5414363075714
-----	---------------

Dimensions

Product Net Weight	.328 lb 148.753 g
--------------------	----------------------

Container Information

Package Level 1 Units	25 piece
Package Level 1 Width	5 in 127 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth /	8 in

Length	203 mm
Package Level 2 Units	50 piece
Package Level 2 Width	5.19 in 132 mm
Package Level 2 Height	8.13 in 207 mm
Package Level 2 Depth / Length	8.49 in 216 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	INSULATED FITTING FOR CONDUIT
Product Type	Connectors-45 Degree
Size	1/2 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210053424

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Declaration of Conformity - CE	9AKK107492A9884
Instructions and Manuals	5342

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

