

PRODUCT-DETAILS

**5343**

**3/4IN INSUL 45 DEGREE LIQ TIGHT CON**



**General Information**

Extended Product Type	5343
Product ID	7TAD012140R0006
EAN	5414363075721
Catalog Description	3/4IN INSUL 45 DEGREE LIQ TIGHT CON
Long Description	3/4 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

**Ordering**

EAN	5414363075721
-----	---------------

**Dimensions**

Product Net Weight	.375 lb 170.068 g
--------------------	----------------------

**Container Information**

Package Level 1 Units	10 piece
Package Level 1 Width	4.5 in 114 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth /	6 in

Length	152 mm
Package Level 2 Units	50 piece
Package Level 2 Width	4.81 in 122 mm
Package Level 2 Height	6.31 in 160 mm
Package Level 2 Depth / Length	21.44 in 545 mm

---

### Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	INSULATED FITTING FOR CONDUIT
Product Type	Connectors-45 Degree
Size	3/4 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210053431

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Declaration of Conformity - CE	9AKK107492A9884
Instructions and Manuals	5343

---

### Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

---

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

