

PRODUCT-DETAILS

5345

1.25 IN INSUL 45 DEG LIQTIGHT CONN



General Information

Extended Product Type	5345
Product ID	7TAD012170R0006
EAN	5414363075745
Catalog Description	1.25 IN INSUL 45 DEG LIQTIGHT CONN
Long Description	1-1/4 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

Ordering

EAN	5414363075745
-----	---------------

Dimensions

Product Net Weight	.98 lb 444.444 g
--------------------	---------------------

Container Information

Package Level 1 Units	5 piece
Package Level 1 Width	5 in 127 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth /	8 in

Length	203 mm
Package Level 2 Units	25 piece
Package Level 2 Width	5.19 in 132 mm
Package Level 2 Height	8.13 in 207 mm
Package Level 2 Depth / Length	20.81 in 529 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	INSULATED CONDUIT FTG, THREADED
Product Type	Connectors-45 Degree
Size	1-1/4 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210053455

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Declaration of Conformity - CE	9AKK107492A9884
Instructions and Manuals	5345

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

