

PRODUCT-DETAILS

5347

2 IN INSUL 45 DEGREE LIQ TIGHT CONN



General Information

Extended Product Type	5347
Product ID	7TAD012170R0010
EAN	5414363099994
Catalog Description	2 IN INSUL 45 DEGREE LIQ TIGHT CONN
Long Description	2 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

Ordering

EAN	5414363099994
-----	---------------

Dimensions

Product Net Weight	2.195 lb 995.465 g
--------------------	-----------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	4.5 in 114 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth /	6 in

Length	152 mm
Package Level 2 Units	5 piece
Package Level 2 Width	4.81 in 122 mm
Package Level 2 Height	6.31 in 160 mm
Package Level 2 Depth / Length	21.44 in 545 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	INSULATED FITTING FOR CONDUIT
Product Type	Connectors-45 Degree
Size	2 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210053479

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Declaration of Conformity - CE	9AKK107492A9884
Instructions and Manuals	5347

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

