

PRODUCT-DETAILS

5355

1.25 IN INSUL 90 DEG LIQ TIGHT CONN



General Information

Extended Product Type	5355
Product ID	7TAD012170R0012
EAN	5414363075806
Catalog Description	1.25 IN INSUL 90 DEG LIQ TIGHT CONN
Long Description	1-1/4 Inch 90 Degree Malleable Iron Insulated Liquidtight Connector

Ordering

EAN	5414363075806
-----	---------------

Dimensions

Product Net Weight	1.19 lb 539.683 g
--------------------	----------------------

Container Information

Package Level 1 Units	5 piece
Package Level 1 Width	6.5 in 165 mm
Package Level 1 Height	4.5 in 114 mm
Package Level 1 Depth /	9.5 in

Length	241 mm
Package Level 2 Units	25 piece
Package Level 2 Width	7.4 in 188 mm
Package Level 2 Height	10.5 in 267 mm
Package Level 2 Depth / Length	23.94 in 608 mm

Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	INSULATED CONDUIT FTG, THREADED
Product Type	Connectors-90 Degree
Size	1-1/4 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210053554

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Declaration of Conformity - CE	9AKK107492A9884
Instructions and Manuals	5355

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

