

PRODUCT-DETAILS

**5356**

**1-1/2IN INSUL 90 DEG LIQ TIGHT CONN**



**General Information**

Extended Product Type	5356
Product ID	7TAD012170R0014
EAN	5414363075813
Catalog Description	1-1/2IN INSUL 90 DEG LIQ TIGHT CONN
Long Description	1-1/2 Inch 90 Degree Malleable Iron Insulated Liquidtight Connector

**Ordering**

EAN	5414363075813
-----	---------------

**Dimensions**

Product Net Weight	1.55 lb 702.948 g
--------------------	----------------------

**Container Information**

Package Level 1 Units	2 piece
Package Level 1 Width	5 in 127 mm
Package Level 1 Height	4 in 102 mm
Package Level 1 Depth /	8 in

Length	203 mm
Package Level 2 Units	10 piece
Package Level 2 Width	5.18 in 132 mm
Package Level 2 Height	8.12 in 206 mm
Package Level 2 Depth / Length	20.81 in 529 mm

### Additional Information

Application	Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.
Brand / Label	T&B Liquidtight Fittings
Material	Malleable Iron
Number of Batteries	0
Product Name	T&B LIQUIDTIGHT FITTINGS
Product Type	Connectors-90 Degree
Size	1-1/2 Inch
Standards	UL E23018, CSA
Surface Finishing	Electro Zinc Plated/Chromate Coating
UPC	786210053561

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000122
Declaration of Conformity - CE	9AKK107492A9884
Instructions and Manuals	5356

### Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121420
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4585 >> Liquid tight connectors

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

