

PRODUCT-DETAILS

LTC125GY

1-1/4IN LT TYPE B COND PVC GRY



General Information

Extended Product Type	LTC125GY
Product ID	7TAD012620R0008
EAN	5414363155140
Catalog Description	1-1/4IN LT TYPE B COND PVC GRY
Long Description	Commercial Grade, Type B Liquidtight Flexible PVC Conduit, 1-1/4 Inch Conduit Size, Approved for Outdoor and Direct Burial in the US, UL Temperature Ratings - 80 Degrees C Dry, 60 Degree C Wet, 70 Degree C Oil, Oil Resistant, Voltage Rating 600V, Gray

Ordering

EAN	5414363155140
-----	---------------

Dimensions

Product Net Depth / Length	30.5 m
Product Net Weight	.379 lb 171.882 g

Container Information

Package Level 2 Units	100 ft
Package Level 2 Width	7.5 in

	191 mm
Package Level 2 Height	28.5 in
	724 mm
Package Level 2 Depth / Length	30.7 in
	780 mm

Additional Information

Application	Machine Tools, Motor Hookups, Food Processing Equipment, Extensions from Wire Ways, and Sensor and Micro Switch Wiring Found In Control Consoles.
Brand / Label	T&B Liquidtight Fittings
Color	Gray
Inside Diameter	35.1 mm
Material	PVC
Nominal Size	1-1/4 in
Number of Batteries	0
Outside Diameter	42.2 mm
Product Name	FLEXIBLE PLASTIC CONDUIT
Product Type	Liquidtight Flexible Non-Metallic Conduit
Special Functions	The Smooth Inner Surface Ensures that Cables and Conductors Can Be Fed Through Very Easily
Standards	UL E95745, CSA
UPC	786210880808
Voltage Rating	600 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000138
Instructions and Manuals	LTC125GY

Classifications

ETIM 6	EC001177 - Protective plastic hose
ETIM 7	EC001177 - Protective plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

