

PRODUCT-DETAILS

LTC200GY

L T NON-MET CONDUIT



General Information

Extended Product Type	LTC200GY
Product ID	7TAD012620R0010
EAN	5414363155188
Catalog Description	L T NON-MET CONDUIT
Long Description	Commercial Grade, Type B Liquidtight Flexible PVC Conduit, 2 Inch Conduit Size, Approved for Outdoor and Direct Burial in the US, UL Temperature Ratings - 80 Degrees C Dry, 60 Degree C Wet, 70 Degree C Oil, Oil Resistant, Voltage Rating 600V, Gray

Ordering

EAN	5414363155188
-----	---------------

Dimensions

Product Net Depth / Length	15.2 m
Product Net Weight	.701 lb 317.914 g

Container Information

Package Level 2 Units	50 ft
Package Level 2 Width	33 in

	838 mm
Package Level 2 Height	9.5 in
	241 mm
Package Level 2 Depth / Length	33 in
	838 mm

Additional Information

Application	Machine Tools, Motor Hookups, Food Processing Equipment, Extensions from Wire Ways, and Sensor and Micro Switch Wiring Found In Control Consoles.
Brand / Label	T&B Liquidtight Fittings
Color	Gray
Inside Diameter	51.3 mm
Material	PVC
Nominal Size	2 in
Number of Batteries	0
Outside Diameter	60.3 mm
Product Name	FLEXIBLE PLASTIC CONDUIT
Product Type	Liquidtight Flexible Non-Metallic Conduit
Special Functions	The Smooth Inner Surface Ensures that Cables and Conductors Can Be Fed Through Very Easily
Standards	UL E95745, CSA
UPC	786210880884
Voltage Rating	600 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000138
Instructions and Manuals	LTC200GY

Classifications

ETIM 6	EC001177 - Protective plastic hose
ETIM 7	EC001177 - Protective plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

