




PRODUCT-DETAILS

LTGUS06G-B

LFMC GP UL 1-1/2IN GRY 15M/50FT



General Information

Extended Product Type	LTGUS06G-B
Product ID	7TAA012LNOR0005
EAN	5415022391183
Catalog Description	LFMC GP UL 1-1/2IN GRY 15M/50FT
Long Description	Liquid Tight Flexible Metallic Conduit, General Purpose, Galvanised Steel Core with PVC Jacket, Conduit Size 1-1/2 Inch, Length 15 Meters/50 Feet, Working Temperature - 30 to 80 Degrees C, UL E125517, CSA LR-72635, Compliant to RoHS, Gray

Ordering

EAN	5415022391183
-----	---------------

Dimensions

Product Net Depth / Length	50 ft 15 m
Product Net Weight	1.04 lb 471.655 g

Container Information

Package Level 2 Units	50 ft
Package Level 2 Width	37 in 940 mm

Package Level 2 Height	10.38 in 264 mm
Package Level 2 Depth / Length	33.62 in 854 mm

Additional Information

Application	General Purpose
Brand / Label	T&B Liquidtight Fittings
Color	Gray
Inside Diameter	1.575 in
Material	Galvanised Steel
Nominal Size	1-1/2 in
Number of Batteries	0
Outside Diameter	1.900 in
Product Name	Flex conduit of steel w/o fittings
Product Type	Liquid Tight Flexible Metallic Conduit
Radius	114 mm
Special Functions	High quality cores and jackets for excellent strength and durability
Standards	UL E125517, CSA LR-72635, RoHS
Surface Finishing	PVC Jacket
UPC	786210108810

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000001
Declaration of Conformity - CE	9AKK107492A9887
Instructions and Manuals	LTGUS06G-B

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Liquidtight Fittings

