

PRODUCT-DETAILS

2920NM

.5 INCH NYLON RANGER CONN .125-.375



General Information

Extended Product Type	2920NM
Product ID	7TAD105200R0000
EAN	5414363101710
Catalog Description	.5 INCH NYLON RANGER CONN .125-.375
Long Description	Liquidtight Strain Relief Connector, Straight, 1/2 Inch NPT Thread, Cable Range 0.125 Inch/3.2mm to 0.375 Inch/9.5mm, Throat Diameter 0.55 Inch, IP65 Rating, UV Resistant Polyamide 6.6 Body, Black

Ordering

EAN	5414363101710
-----	---------------

Dimensions

Product Net Weight	.05 lb 22.676 g
--------------------	--------------------

Container Information

Package Level 1 Units	25 piece
Package Level 1 Width	5 in 127 mm
Package Level 1 Height	4 in

	102 mm
Package Level 1 Depth / Length	6 in 152 mm
Package Level 2 Units	100 piece
Package Level 2 Width	8.75 in 222 mm
Package Level 2 Height	5.5 in 140 mm
Package Level 2 Depth / Length	12.75 in 324 mm

Additional Information

Application	A Liquidtight Fitting to Secure Flexible Cord or Power Cable to a Box or Enclosure and Provide Strain Relief
Brand / Label	T&B Cord & Cable Fittings
Color	Black
Material	Polyamide/Nylon 6.6
Number of Batteries	0
Product Name	T&B CORD FITTINGS
Product Type	Cord Connectors-Straight
Size	1/2 Inch
Special Functions	Extended Range with Superior Strain Relief
Standards	UL E13938, CSA 52391
Temperature Range	-34 to +105 °C
UPC	786210797403

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000050
Instructions and Manuals	2920NM

Classifications

ETIM 6	EC000441 - Cable screw gland
ETIM 7	EC000441 - Cable gland
UNSPSC	39121431
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4601 >> Cable gland connector

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

