


PRODUCT SPECIFICATION DRAWING

TESTRITE® TR4-PVC-NH


Combination Test Tee & Cleanout



The TESTRITE® TR4-PVC-NH installs in-line between DWV sections and allows the DWV line to be temporarily blocked for stack testing. The TESTRITE TR4-PVC-NH includes a PVC TEST and CLEANOUT TEE which remains in the pipe system after test and a CLEANOUT PLUG to cap the opening and preserve a smooth flow path. It is designed to be used with the removable & reusable TESTRITE TR4-TWV TEST WEDGE, which allows temporary blocking of the DWV stack for testing while providing connections for convenient system fill and drain. Drain flow may be interrupted, e.g., for partial tests, by opening and closing an integral valve in the TR4-TWV TEST WEDGE. The TR4-PVC-NH may be used vertically or horizontally. Install as with any normal fitting and follow manufacturer instructions for testing. Remains in the system as a cleanout and for future testing.

Product Information:

- Material:
 Cleanout Tee: PVC, Black
 Cleanout Plug: NYLON 6/6, Green
 Spanner Ring: PVC, Black
- Complies with ASTM-D2665; compatible with cast iron fittings per ASTM-A888
- Pressure rating (max): 15 psi (water) / 5 psi (air)
- UPC / IAPMO listed
- Does not include TR4-TWV Test Wedge
- Patent Pending



Shown without Spanner Ring

THIS INFORMATION IS PROPRIETARY TO HOLDRITE AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IT MAY NOT BE REPRODUCED IN PART OR WHOLE WITHOUT WRITTEN AUTHORIZATION.



CONVERTING MAKESHIFT METHODS INTO ENGINEERED SOLUTIONSSM
 800-321-0316 OR 760-744-6944 / FAX: 760-744-0507 / WWW.HOLDRITE.COM
 spec_TR4-PVC-NH_RevC

Product Submittal	
Job Name:	
Date:	
Part Number:	Qty:
Architect / Owner:	
Contractor:	
Notes:	