

Commercial Elongated Open Front Toilet Seat w/Stainless Steel Check-Hinge Post (White)

Before You Begin:

1. Check Contents:

Ensure you have all the parts included with your Bluefin Toilet Seat

- Pair of Rectangular gaskets
- Pair of Rubber washers
- Pair of Flat washers
- Pair of Lock washers
- Pair of Hex nuts

2. Prior to Beginning Installation:

Tools Required

- Adjustable wrench or 1/2" socket wrench
- (Optional) Screwdriver to help align bolts

EASY TO INSTALL ASSEMBLY INSTRUCTIONS:

1. Position the Seat:

- Lift the seat into the **upright (vertical)** position, as shown in the diagram.
- Align the **hinge posts** with the bolt holes on the toilet bowl.

2. Install the Rectangular Gaskets:

- Slide a **rectangular gasket** onto each hinge post.
- Rest the gasket flat on the top surface of the toilet bowl around the bolt holes.
 - *These help stabilize the hinge and prevent damage to the bowl.*

3. Insert the Seat Bolts:

- Insert each hinge bolt **down through** the holes in the toilet bowl.
 - Make sure the seat remains centered.

4. Assemble Washers Under the Bowl

- On the underside of the toilet bowl, install hardware in this order (**top to bottom**)
 - *Rubber washer* – protects porcelain, helps grip
 - *Flat washer* – distributes pressure
 - *Lock washer* – prevents loosening
 - *Hex nut* – secures the assembly
 - *Repeat for both sides as shown in the diagram*

5. Tighten the Nuts

- Hand-tighten the hex nuts first.
- Use a wrench to snug them
 - **DO NOT overtighten**, as this can crack porcelain or damage the seat hinges.
- Ensure the seat moves freely and stays aligned when lowered.

6. Final Check

- Raise and lower the seat several times to ensure smooth movement.
- Sit gently on the seat to confirm it does not wobble
- Re-tighten slightly if any movement is noticed.

