

Slow Close Plastic Elongated Toilet Seat (White)

Before You Begin:

1. Check Contents:

Ensure you have all the parts included with your Bluefin Toilet Seat

- Seat and lid assembly
- Hinges and hinge covers
- Mounting bolts and nuts

2. Verify Seat Size

Measure your toilet bowl to confirm the correct seat size:

- **Elongated bowl:**
 - Mounting holes: 5½ inches apart
 - Length: 18½ inches from holes to front of bowl
- **Round (standard) bowl:**
 - Mounting holes: 5½ inches apart
 - Length: 16½ inches from holes to front of bowl

EASY TO INSTALL ASSEMBLY INSTRUCTIONS:

ONLY A SCREWDRIVER IS REQUIRED FOR INSTALLATION:

1. Position the Seat:

- Align the seat's hinge posts with the toilet bowl mounting holes.

2. Insert Mounting Screws:

- Place a screw through each hinge post slot and into the bowl mounting holes.
- From underneath the bowl, start threading the nut onto each screw conical side up.

3. Tighten the Screws:


- Hold the nut underneath the bowl.
- Using a slotted screwdriver from above, tighten the screw until the nut contacts the bowl and stops turning.
- Once the nut is snug, you can release your hold underneath.

4. Align and Secure the Seat:

- Check the seat alignment and adjust as needed.
- Tighten both bolts fully.

5. Lock the Hinges:

- Close and lock each hinge cover into place.



Maintenance:

1. Periodic Check:

- Regularly inspect and retighten the bolts to ensure stability

2. Cleaning:

- Clean using a soft damp cloth and mild soap only. *Avoid harsh chemicals, abrasives, or bleach, which can damage the surface.*