

Product Specifications


Performance

6/13/2023

Model: AE2410Y-AA1A

Product Description

Type: Reciprocating Compressors
Application: LBP - Low Back Pressure
Refrigerant: R-134a/R-513A
Voltage/Frequency: 115V ~ 60Hz
Version: N/A



Condition	Test Voltage	Refrigeration Capacity		Input Power (E)		Efficiency		W/W	EVAP TEMP Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W	(I) W	(E) Btu/Wh	(E) kcal/Wh					
ASHRAE (R-134a)	115V ~ 60HZ	950	239	278	237	4.01	1.01	1.17	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)
ASHRAE (R-513A)	115V ~ 60HZ	1168	294	342	277	4.21	1.06	1.23	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)
ASHRAE (R-134a)	115V ~ 60HZ	950	239	278	237	4.01	1.01	1.17	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)
ASHRAE (R-513A)	115V ~ 60HZ	1168	294	342	277	4.21	1.06	1.23	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)

General

Evaporating Temp. Range: -40°C to -10°C (-40°F to 14°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 10
Weight Unit of Measure: KG
Displacement (cc): 9.39
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 285

Electrical

Voltage Range (50 Hz):
Voltage Range (60 Hz): 103-127
Locked Rotor Amps (LRA): 28.5
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 3.11
Max. Continuous Current (MCC in Amps): 5.22
Motor Resistance (Ohm) - Main: 2.32
Motor Resistance (Ohm) - Start: 4.55
MotorType: CSIR
Overload Type:
Relay Type:

Agency Approval

cURus Recognized