

Technical Datasheet

Product Specifications


Performance

6/11/2023

Model: AE4440Z-AA1A

Product Description

Type: Reciprocating Compressors
Application: HBP/CBP - High/Commercial Back Pressure
Refrigerant: R-404A/R-407A/R-448A/R-449A/R-452A
Voltage/Frequency: 115V ~ 60Hz
Version: N/A



Condition	Test Voltage	Refrigeration Capacity		Input Power (E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP		
		(R) Btu/h	(R) kcal/h	(R) W	(I) W	(E) Btu/Wh						(E) kcal/Wh	W/W
ASHRAE (R-407A)	115V ~ 60HZ	4046	1020	1186	512	7.9	1.99	2.32	7.2?C (45? F)	54?C (130? F)	35?C (95?F)	35?C (95? F)	46?C (115? F)
ASHRAE (R-449A)	115V ~ 60HZ	4270	1077	1251	515	8.29	2.09	2.43	7.2?C (45? F)	54?C (130? F)	35?C (95?F)	35?C (95? F)	46?C (115? F)
ASHRAE (R-448A)	115V ~ 60HZ	4270	1077	1251	515	8.29	2.09	2.43	7.2?C (45? F)	54?C (130? F)	35?C (95?F)	35?C (95? F)	46?C (115? F)
ASHRAE (R-452A)	115V ~ 60HZ	4112	1037	1205	539	7.63	1.92	2.24	7.2?C (45? F)	54?C (130? F)	35?C (95?F)	35?C (95? F)	46?C (115? F)
ASHRAE (R-404A)	115V ~ 60HZ	4350	1096	1275	563	7.73	1.95	2.26	7.2?C (45? F)	54?C (130? F)	35?C (95?F)	35?C (95? F)	46?C (115? F)
ASHRAE (R-407A)	115V ~ 60HZ	4046	1020	1186	512	7.9	1.99	2.32	7.2?C (45? F)	54?C (130? F)	35?C (95?F)	35?C (95? F)	46?C (115? F)
ASHRAE (R-449A)	115V ~ 60HZ	4270	1077	1251	515	8.29	2.09	2.43	7.2?C (45? F)	54?C (130? F)	35?C (95?F)	35?C (95? F)	46?C (115? F)
ASHRAE (R-448A)	115V ~ 60HZ	4270	1077	1251	515	8.29	2.09	2.43	7.2?C (45? F)	54?C (130? F)	35?C (95?F)	35?C (95? F)	46?C (115? F)
ASHRAE (R-452A)	115V ~ 60HZ	4112	1037	1205	539	7.63	1.92	2.24	7.2?C (45? F)	54?C (130? F)	35?C (95?F)	35?C (95? F)	46?C (115? F)
ASHRAE (R-404A)	115V ~ 60HZ	4350	1096	1275	563	7.73	1.95	2.26	7.2?C (45? F)	54?C (130? F)	35?C (95?F)	35?C (95? F)	46?C (115? F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 10
Weight Unit of Measure: KG
Displacement (cc): 6.69
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 285

Electrical

Voltage Range (50 Hz):
Voltage Range (60 Hz): 103-127
Locked Rotor Amps (LRA): 36
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 6.3
Max. Continuous Current (MCC in Amps): 7.78
Motor Resistance (Ohm) - Main: 1.37
Motor Resistance (Ohm) - Start: 3.85
MotorType: CSIR
Overload Type:
Relay Type:

Agency Approval

