

Model: AE4440A-AA1A

Product Description

Type:	Reciprocating Compressors
Application:	HBP/CBP - High/Commercial Back Pressure
Refrigerant:	R-12
Voltage/Frequency:	115V ~ 60Hz
Version:	N/A



Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ASHRAE (R-12)	115V ~ 60HZ	3987	1005	1169	575	6.94	1.75	2.03	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE (R-12)	115V ~ 60HZ	3987	1005	1169	575	6.94	1.75	2.03	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	10
Weight Unit of Measure:	KG
Displacement (cc):	10.33
Oil Type:	Synthetic Alkylate
Viscosity (cSt):	32
Oil Charge (cc):	380

Electrical

Voltage Range (50 Hz):	
Voltage Range (60 Hz):	103-127
Locked Rotor Amps (LRA):	32
Rated Load Amps (RLA 50 Hz):	0
Rated Load Amps (RLA 60 Hz):	5.82
Max. Continuous Current (MCC in Amps):	8.16
Motor Resistance (Ohm) - Main:	1.65
Motor Resistance (Ohm) - Start:	3.44
Motor Type:	CSIR
Overload Type:	
Relay Type:	

Agency Approval

CE Listed, cURus Recognized