

XS-MINI Pressure Washer

Cordless, Portable, Foldable

- Includes Various Nozzle Heads
- Water Tank Capacity: 12 L
- Hose Length: 2.5 m (8.2 ft)
- Power Source: 2000 mAh rechargeable lithium battery
- Battery Life: 35 min
- Working Voltage: 12 V
- Working Pressure: 72 PSI $\pm$ 10
- IP Rating: IPX4 water resistant



Two Nozzle Heads



Inspection Camera Accessories



Hard Carrying Case
All NTS Cameras



Soft Carrying Case
TD500 & TD450s Cameras



Soft Carrying Case
TF550 Camera



Hook & Magnet
Standard Cameras



Hook & Magnet
Articulating Cameras



Monitor Stand
NTS500B Camera



32 GB microSD Memory Card
Inspection Cameras



USB-C Cable
All Products

About Us

Founded in 2010, Teslong designs advanced tools and technology for professionals and DIYers across a wide range of industries, including automotive, HVAC, plumbing, and hunting. Our product lineup includes inspection cameras, thermal cameras, borescopes, and everyday tools, as well as a PRO Series engineered for high-demand professional work.

Our mission is to lead with innovation and deliver tools that make every job easier, smarter, and more effective, backed by an R&D team of over 20 engineers and cutting-edge production lines.

Built to tackle tough jobs and uncover hidden issues — Teslong helps you “See the Solution!”



TESLONG



www.teslong.com

www.teslong.com

NTS300 & NTS500 Standard Probes

Single Lens 3.9 mm (0.15 in) Probe

- Probe Type: Flexible and semi-rigid
- Probe Length: 1 m (3.2 ft) and 3 m (9.8 ft)
- Field of View: 70°
- Focus Range: 3–8 cm (1.18–3.15 in)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 6 front
- Interchangeable with NTS300 and NTS500

Dual Lens 5.5 mm (0.21 in) Probe

- Probe Type: Flexible and semi-rigid
- Probe Length: 1 m (3.2 ft), 3 m (9.8 ft), and 5 m (16.4 ft)
- Field of View: 78°
- Focus Range:
 - A: 3–8 cm (1.18–3.15 in)
 - B: 2–5 cm (0.79–1.97 in)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 6 front and 1 side
- Interchangeable with NTS300 and NTS500

Triple Lens 7.9 mm (0.31 in) Probe

- Probe Type: Flexible and semi-rigid
- Probe Length: 1 m (3.2 ft), 3 m (9.8 ft), and 5 m (16.4 ft)
- Field of View: 78°
- Focus Range:
 - A: 3–8 cm (1.18–3.15 in)
 - B: 2–5 cm (0.79–1.97 in)
 - C: 1.5–3 cm (0.59–1.18 in)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 8 front and 2 side
- Interchangeable with NTS300 and NTS500

Rotating Dual Lens 8.5 mm (0.33 in) Probe

- 360° Motorized Rotating Camera Head
- Probe Type: Flexible and semi-rigid
- Probe Length: 1 m (3.2 ft), 3 m (9.8 ft), and 5 m (16.4 ft)
- Field of View: 90° + rotating
- Focus Range: 1.5–8 cm (0.59–3.15 in)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 8 front and 1 side
- Interchangeable with NTS300 and NTS500

NTS500B USB-C Standard Probe

USB-C Dual Lens 5 mm (0.19 in) Probe

- USB-C Standard Connection
- Probe Type: Flexible and semi-rigid
- Probe Length: 5 m (16.4 ft)
- Field of View: 70°
- Focus Range:
 - A: 3–8 cm (1.18–3.15 in)
 - B: 2–5 cm (0.79–1.97 in)
- Megapixels: 2.0 MP
- Adjustable Camera Light LEDs: 6 front and 1 side

Standard Monitors

NTS300 Monitor

- Screen Type: 5-inch IPS screen
- Screen Resolution: 854x480
- Image Resolution: 1920x1080 (Full HD)
- Video Resolution: 1280x720 (HD)
- Image Zoom: 1.3x–1.5x
- Integrated Work Light: 1 watt Cree LED
- Ports: USB-C charge/data port and microSD card slot
- Power Source: 5000 mAh rechargeable lithium battery
- Battery Life: 4–5 hours

NTS500 Monitor

- Screen Type: 5-inch IPS screen
- Screen Resolution: 1280x720 (HD)
- Image Resolution: 1920x1080 (Full HD)
- Video Resolution: 1280x720 (HD)
- Integrated Work Light: 1 watt Cree LED
- Ports: USB-C charge/data port and microSD card slot
- Power Source: 3500 mAh rechargeable lithium battery
- Battery Life: 2–4 hours

NTS500B USB-C Monitor

- Screen Type: 5-inch IPS screen
- Screen Resolution: 854x480
- Image Resolution: 1920x1080 (Full HD)
- Video Resolution: 1280x720 (HD)
- Image Zoom: 1.3x–1.5x
- Integrated Work Light: 1 watt Cree LED
- Ports: USB-C charge/data port and microSD card slot
- Power Source: 3500 mAh rechargeable lithium battery
- Battery Life: 2–4 hours

Articulating Monitors

TD450s Articulating Monitor (2-Way)

- Screen Type: 4.5-inch IPS screen
- Screen Resolution: 854x480
- Image Resolution: 1920x1080 (Full HD)
- Video Resolution: 1280x720 (HD)
- Image Zoom: 1.3x–1.5x
- Ports: USB-C charge/data port and microSD card slot
- Power Source: 3000 mAh rechargeable lithium battery
- Battery Life: 3–4 hours
- Wi-Fi Remote Viewing: Supported

TD500 Articulating Monitor (2-Way)

- Screen Type: 5-inch IPS screen
- Screen Resolution: 854x480
- Image Resolution: Max 1920x1080 (Full HD)
- Video Resolution: Max 1920x1080 (Full HD)
- Image Zoom: 1.3x–1.5x
- Split Screen: Supported (Dual lens 6.5 mm (0.25 in) only)
- Ports: USB-C charge/data port and microSD card slot
- Power Source: 3000 mAh rechargeable lithium battery
- Battery Life: 3–4 hours
- Wi-Fi Remote Viewing: Supported

TF550 Articulating Monitor with Joystick (4-Way)

- Screen Type: 5-inch IPS screen
- Screen Resolution: 854x480
- Image Resolution: Max 1920x1080 (Full HD)
- Video Resolution: Max 1920x1080 (Full HD)
- Image Zoom: 1.3x–1.5x
- Ports: USB-C charge/data port and microSD card slot
- Power Source: 3000 mAh rechargeable lithium battery
- Battery Life: 3–4 hours
- Wi-Fi Remote Viewing: supported
- Modular Structure with Detachable Monitor

TD450s 2-Way Articulating Probes

Single Lens 8.5 mm (0.33 in) Probe

- Probe Type: Flexible and semi-rigid
- Probe Length: 1.5 m (5 ft)
- Field of View: 70°
- Focus Range: 2–10 cm (0.79–3.94 in)
- Megapixels: 2.0 MP
- Adjustable Camera Light LEDs: 8 front

Dual Lens 8.5 mm (0.33 in) Probe

- Probe Type: Flexible and semi-rigid
- Probe Length: 1.5 m (5 ft)
- Field of View: 70°
- Focus Range:
 - A: 2–10 cm (0.79–3.94 in)
 - B: 1–7 cm (0.39–2.76 in)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 8 front and 1 side

TD500 2-Way Articulating Probes

Single Lens 3.9 mm (0.15 in) Probe

- Probe Type: Flexible and semi-rigid
- Probe Length: 1.5 m (5 ft)
- Field of View: 80°
- Focus Range: 2–10 cm (0.79–3.94 in)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 6 front

Single Lens 8.5 mm (0.33 in) Probe

- Probe Type: Flexible and semi-rigid
- Probe Length: 1.5 m (5 ft)
- Field of View: 70°
- Focus Range: 2–10 cm (0.79–3.94 in)
- Megapixels: 2.0 MP
- Adjustable Camera Light LEDs: 8 front

Dual Lens 6.5 mm (0.25 in) Probe

- Probe Type: Flexible and semi-rigid
- Probe Length: 1.5 m (5 ft)
- Field of View: 90°
- Focus Range: 1 cm–∞ (0.39 in–∞)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 6 front and 1 side

TF550 4-Way Articulating Probe

Dual Lens 6.5 mm (0.25 in) Probe

- Probe Type: Flexible and semi-rigid
- Probe Length: 1.5 m (5 ft)
- Field of View: 90°
- Focus Range: 1 cm–∞ (0.39 in–∞)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 6 front and 1 side