

BUILT FOR THE DIRTY WORK



Liquid
Resistant



Heat Resistant
Up to 130 °F




Bright Adjustable
LED Lights

Accessories



Hard Carrying Case
Inspection Cameras



Soft Carrying Case
Thermal Cameras



Hook & Magnet
T6, N7, F5, F6 PRO Cameras



Hook & Magnet
T7 PRO Camera



Monitor Stand
N7 PRO Camera



Wrist Strap
Thermal Cameras



32 GB microSD Memory Card
Inspection Cameras



USB-C Cable
All products

About Us

Founded in 2010, Teslong designs advanced tools and technology for professionals and DIYers across a wide range of industries, including automotive, HVAC, plumbing, and hunting. Our product lineup includes inspection cameras, thermal cameras, borescopes, and everyday tools, as well as a PRO Series engineered for high-demand professional work.

Our mission is to lead with innovation and deliver tools that make every job easier, smarter, and more effective, backed by an R&D team of over 20 engineers and cutting-edge production lines.

Built to tackle tough jobs and uncover hidden issues — Teslong helps you “See the Solution!”



TESLONG

PRO SERIES



www.teslong.com

www.teslong.com

PRO Detachable Cameras

T6 PRO Inspection Camera Triple Lens 7.9 mm (0.31 in) Probe

- Screen Type: 6-inch IPS screen
- Screen Resolution: 1280x720 (HD)
- Split Screen: Supported
- Image Rotation: 180°
- Image Resolution: Max 1920x1080 (Full HD)
- Video Resolution: Max 1920x1080 (Full HD)
- Integrated Work Light: 1 watt Cree LED
- IP54-Rated Monitor: Dust and water resistant
- Probe Type: Flexible and semi-rigid
- Probe Length: 2 m (6.5 ft)
- Field of View: 78°
- Focus Range:
 - A: 3–8 cm (1.18–3.15 in)
 - B: 2–5 cm (0.79–1.97 in)
 - C: 1.5–3 cm (0.59–1.18 in)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 8 front and 2 side
- Wi-Fi Remote Viewing: Supported
- Ports: USB-C charge/data port and microSD card slot
- Power Source: 6000 mAh rechargeable lithium battery
- Battery Life: About 4 hours
- Detachable Probe



T7 PRO Inspection Camera 360° Rotating Dual Lens 8.5 mm (0.33 in) Probe

- Screen Type: 6-inch IPS screen
- Screen Resolution: 1280x720 (HD)
- Split Screen: Supported
- Image Rotation: 180°
- Image Resolution: Max 1920x1080 (Full HD)
- Video Resolution: Max 1920x1080 (Full HD)
- Integrated Work Light: 1 watt Cree LED
- IP54-Rated Monitor: Dust and water resistant
- Probe Type: Flexible and semi-rigid
- Probe Length: 2 m (6.5 ft)
- Field of View: 90° + rotating
- Focus Range: 1.5 cm–∞ (0.59 in–∞)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 8 front and 1 side
- Wi-Fi Remote Viewing: Supported
- Ports: USB-C charge/data port and microSD card slot
- Power Source: 6000 mAh rechargeable lithium battery
- Battery Life: About 4 hours
- Detachable Probe



N7 PRO Inspection Camera Dual Lens 5.5 mm (0.21 in) Probe

- Screen Type: 7-inch IPS screen
- Screen Resolution: 1280x720 (HD)
- Split Screen: Supported
- Image Rotation: 180°
- Image Resolution: Max 1920x1080 (Full HD)
- Video Resolution: Max 1920x1080 (Full HD)
- Integrated Work Light: 1 Watt Cree LED
- Probe Type: Flexible and semi-rigid
- Probe Length: 2 m (6.5 ft)
- Field of View: 68°
- Focus Range:
 - A: 3–8 cm (1.18–3.15 in)
 - B: 2–5 cm (0.79–1.97 in)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 6 front and 1 side
- Wi-Fi Remote Viewing: Supported
- Ports: USB-C charge/data port and microSD card slot
- Power Source: 6000 mAh rechargeable lithium battery
- Battery Life: About 3.5 hours
- Detachable Probe



All probes are IP67-rated, dustproof, and waterproof up to 1 m (3 ft) for 30 minutes.
All inspection cameras have 32 GB microSD memory card storage.

PRO Thermal Cameras

M1 PRO Infrared Camera Thermal Imaging

- Screen Type: 3.2-inch TFT LCD screen
- Screen Resolution: 240x320
- Integrated Work Light: 2 LEDs
- Laser Pointer: Class II
- Color Spectrum: 8 modes (iron, white hot, black hot, rainbow, hottest, high contrast, green hot, lava)
- Thermal AGC: Smooth, normal, high contrast
- Temperature Display: Center point, max (hot), min (cold), zone
- Infrared Sensor Resolution: 120x90
- Frame Rate: 25 fps
- Field of View: 38°–50°
- Pixel Size: 17 µm
- Spectral Range: 8–14 µm
- Temperature Measurement Range: –20 to 400 °C (–4 to 752 °F)
- Temperature Measurement Accuracy: ±2 °C or ±2% of reading
- Ports: USB-C charge/data port
- Memory Storage: 8 GB internal storage (approx. 20,000 images)
- Power Source: 2800 mAh rechargeable lithium battery
- Battery Life: 3.5 hours
- ¼ in Tripod Screw Mount: Supported



M2 PRO Infrared Camera Thermal Imaging

- Screen Type: 3.2-inch TFT LCD screen
- Screen Resolution: 480x640
- Integrated Work Light: 2 LEDs
- Laser Pointer: Class II
- Image Modes: 7 modes (thermal, visible, outline fusion, overlay fusion, PIP, fusion adj., offset adj.)
- Color Spectrum: 8 modes (iron, white hot, black hot, rainbow, hottest, high contrast, green hot, lava)
- Thermal AGC: Smooth, normal, high contrast
- Temperature Display: Center point, max (hot), min (cold), zone
- Infrared Sensor Resolution: 256x192
- Frame Rate: 25 fps
- Field of View: 42°–56°
- Pixel Size: 12 µm
- Spectral Range: 8–14 µm
- Temperature Measurement Range: –20 to 550 °C (–4 to 1022 °F)
- Temperature Measurement Accuracy: ±2 °C or ±2% of reading
- Ports: USB-C charge/data port
- Memory Storage: 8 GB internal storage (20,000 images)
- Power Source: 2800 mAh rechargeable lithium battery
- Battery Life: 3.5 hours
- ¼ in Tripod Screw Mount: Supported



All thermal cameras are IP54-rated for dust and water resistance.

PRO Articulating Cameras

F5 PRO Articulating Inspection Camera 2-Way Dual Lens 6.5 mm (0.25 in) Probe

- Screen Type: 5-inch IPS screen
- Screen Resolution: 854x480
- Split Screen: Supported
- Image Rotation: 180°
- Image Zoom: 1.3x and 1.5x
- Image Resolution: Max 1920x1080 (Full HD)
- Video Resolution: Max 1920x1080 (Full HD)
- Probe Type: Flexible and semi-rigid
- Probe Length: 1.5 m (5 ft)
- Field of View: 90°
- Focus Range: 1 cm–∞ (0.39 in–∞)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 6 front and 1 side
- Wi-Fi Remote Viewing: Supported
- Ports: USB-C charge/data port and microSD card slot
- Power Source: 3000 mAh rechargeable lithium battery
- Battery Life: About 4.5 hours
- Modular Structure with Detachable Monitor



F6 PRO Articulating Inspection Camera with Joystick 4-Way Dual Lens 6.5 mm (0.25 in) Probe

- Screen Type: 6-inch IPS screen
- Screen Resolution: 1920x1080 (Full HD)
- Split Screen: Supported
- Image Rotation: 180°
- Image Zoom: 1.3x and 1.5x
- Image Resolution: Max 1920x1080 (Full HD)
- Video Resolution: Max 1920x1080 (Full HD)
- Integrated Work Light: 1 watt Cree LED
- Probe Type: Flexible and semi-rigid
- Probe Length: 1.5 m (5 ft)
- Field of View: 90°
- Focus Range: 1 cm–∞ (0.39 in–∞)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 6 front and 1 side
- Wi-Fi Remote Viewing: Supported
- Ports: USB-C charge/data port, mini HDMI, and microSD card slot
- Power Source: 6000 mAh rechargeable lithium battery
- Battery Life: About 3.5 hours
- Modular Structure with Detachable Monitor



F8 PRO Articulating Inspection Camera with Joystick 4-Way Single Lens 3.9 mm (0.15 in) Probe

- Screen Type: 6-inch IPS screen
- Screen Resolution: 1920x1080 (Full HD)
- Image Rotation: 180°
- Image Zoom: 1.3x and 1.5x
- Image Resolution: Max 1920x1080 (Full HD)
- Video Resolution: Max 1920x1080 (Full HD)
- Integrated Work Light: 1 watt Cree LED
- Probe Type: Flexible
- Probe Length: 1.5 m (5 ft)
- Field of View: 80°
- Focus Range: 2–10 cm (0.79–3.94 in)
- Megapixels: 1.0 MP
- Adjustable Camera Light LEDs: 6 front
- Wi-Fi Remote Viewing: Supported
- Ports: USB-C charge/data port, mini HDMI, and microSD card slot
- Power Source: 6000 mAh rechargeable lithium battery
- Battery Life: About 3.5 hours
- Modular Structure with Detachable Monitor



All probes are IP67-rated, dustproof, and waterproof up to 1 m (3 ft) for 30 minutes.
All inspection cameras have 32 GB microSD memory card storage.