

Insulated Bonding Bushings

Corrosion Resistant - Malleable Iron

Features

- Hot dip galvanized for superior protection against corrosion
- Tin plated copper lay-in lug
- UV resistant liner for direct exposure to the sun
- Stainless steel hardware

Applications

- Ideal for solar photovoltaic applications.
- Use to provide a means of grounding Rigid or IMC conduit
- Indoor or outdoor use (lay-in lug)
- Use lug provided for bonding jumper to a neutral bus bar
- Prevent damage to wire insulation with the UV resistant liner




Standard Material

- Body – Malleable iron
- Lug – Tin plated copper
- Clamping screw – Stainless steel
- Set screws – Stainless steel

Standard Finish

- Hot dip galvanized



Catalog Number	UPC	Size	Grounding Lug Wire Size		Unit Carton	Ship Case	Weight/Case	Recommended Torque (in - lbs)	Inches	
			Min.	Max					A	B
332MSL	03837	3/4"	14	4	10	100	14	35	1.31	0.57
333MSL	03838	1"	14	4	5	50	9	35	1.61	0.65
334MSL	03840	1-1/4"	14	4	5	50	10	35	1.91	0.71
335MSL	03841	1-1/2"	14	4	5	50	12	35	2.16	0.73
336MSL	03842	2"	14	4	5	50	15	35	2.72	0.73
334AMSL	03853	1-1/4"	14	2/0	5	50	16	35	1.91	0.71
335AMSL	03854	1-1/2"	14	2/0	5	50	17	35	2.16	0.73
336AMSL	03855	2"	14	2/0	5	50	20	35	2.72	0.73