

# Flexible Steel Conduit

## UL Listed Coil



### Features

- Hot dipped galvanized zinc coating
- Corrosion and crush resistant
- Flexibility for simplified positioning
- Smooth interior for easy wire pull-through
- Easy installation to follow contours

### Applications

- Voice, data, communications and video cables
- Motor feeder, branch and control circuit conductors and cables
- Remote-control, signaling and power limited circuit conductors and cables; Class 1-3
- Cables of power-limited or non-power limited fire alarm circuits, fire alarm system conductors
- Environmental air-handling spaces
- Elevators, escalators, and hoistways
- Concealed or exposed installations
- Metal raceway for wires and cables
- Grounding conductor for lengths up to 6 feet



### Standard Material

- Galvanized steel

### Standard Finish

- Hot dip galvanized zinc coating

Catalog Number	UPC	Size	Feet Coil	Ship Case	Weight/ Case	Thickness	Inside Diameter Min.	Inside Diameter Max.	Outside Diameter Min.	Outside Diameter Max.
<b>5200C100UL</b>	87291	<b>3/8"</b>	<b>100'</b>	100	23	.64	.393	.393	.56	.61
<b>5200UL</b>	87292	<b>3/8"</b>	<b>250'</b>	250	59	.64	.393	.393	.56	.61
<b>5201UL</b>	87293	<b>1/2"</b>	<b>100'</b>	100	29	.64	.625	.645	.86	.92
<b>5202UL</b>	87294	<b>3/4"</b>	<b>100'</b>	100	37	.64	.812	.835	1.045	1.105
<b>5203UL</b>	87295	<b>1"</b>	<b>50'</b>	50	31	.76	1	1.04	1.30	1.38
<b>5204UL</b>	87297	<b>1-1/4"</b>	<b>50'</b>	50	34	.76	1.25	1.30	1.55	1.63
<b>5205UL</b>	87298	<b>1-1/2"</b>	<b>25'</b>	25	19	.76	1.50	1.575	1.85	1.95
<b>5206UL</b>	87300	<b>2"</b>	<b>25'</b>	25	22	.76	2	2.08	2.35	2.454
<b>5207UL</b>	87301	<b>2-1/2"</b>	<b>25'</b>	25	44	1.05	2.50	2.70	2.86	3.06
<b>5208UL</b>	87302	<b>3"</b>	<b>25'</b>	25	51	1.05	3	3.20	3.36	3.56
<b>5209UL</b>	87303	<b>3-1/2"</b>	<b>25'</b>	25	61	1.05	3.50	3.50	3.86	4.60
<b>5210UL</b>	87304	<b>4"</b>	<b>25'</b>	25	72	1.05	4	4	4.36	4.56