

# Flexible Steel Conduit

## UL Listed Reel



### Features

- Hot dipped galvanized zinc coating
- Corrosion and crush resistant
- Flexibility for simplified positioning
- Smooth interior for easy wire pull-through
- Easy installation to follow contours

### Applications

- Voice, data, communications and video cables
- Motor feeder, branch and control circuit conductors and cables
- Remote-control, signaling and power limited circuit conductors and cables; Class 1-3
- Cables of power-limited or non-power limited fire alarm circuits, fire alarm system conductors
- Environmental air-handling spaces
- Elevators, escalators, and hoistways
- Concealed or exposed installations
- Metal raceway for wires and cables
- Grounding conductor for lengths up to 6 feet



### Standard Material

- Galvanized steel

### Standard Finish

- Hot dip galvanized zinc coating

Catalog Number	UPC	Size	Feet Reel	Ship Case	Weight/Case	Thickness	Inside Diameter		Outside Diameter	
							Min.	Max.	Min.	Max.
<b>5200RUL</b>	87305	<b>3/8"</b>	<b>1000'</b>	1000	250	.64	.393	.393	.56	.61
<b>5201RUL</b>	87306	<b>1/2"</b>	<b>1000'</b>	1000	316	.64	.625	.645	.86	.92
<b>5201R500UL</b>	87307	<b>1/2"</b>	<b>500'</b>	500	164	.64	.625	.645	.86	.92
<b>5202RUL</b>	87308	<b>3/4"</b>	<b>1000'</b>	1000	397	.64	.812	.835	1.045	1.105
<b>5202R500UL</b>	87309	<b>3/4"</b>	<b>500'</b>	500	203	.64	.812	.835	1.045	1.105
<b>5203RUL</b>	87310	<b>1"</b>	<b>400'</b>	400	265	.76	1	1.04	1.30	1.38
<b>5204RUL</b>	87311	<b>1-1/4"</b>	<b>200'</b>	200	154	.76	1.25	1.30	1.55	1.63
<b>5205RUL</b>	87312	<b>1-1/2"</b>	<b>150'</b>	150	129	.76	1.50	1.575	1.85	1.95
<b>5206RUL</b>	87313	<b>2"</b>	<b>100'</b>	100	107	.76	2	2.08	2.35	2.454