

Flexible Liquidtight Conduit

Metallic - Reel



Features

- Crush and corrosion resistant steel core for lasting mechanical protection
- EF PVC jacket is oil and sunlight resistant
- Smooth interior for easy wire pull through

Applications

- For use in damp or wet locations, suitable for commercial and industrial use
- Non UL

Standard Material

- EF PVC jacketed steel core coil on reel

Catalog Number	UPC	Size	Feet Reel	Ship Case	Weight/Case	Inside Diameter		Outside Diameter	
						Min.	Max.	Min.	Max.
6100R	85588	3/8"	1000'	1000'	182	.484	.504	.689	.709
6101R	82021	1/2"	1000'	1000'	296	.622	.642	.819	.839
6102R	85247	3/4"	500'	500'	148	.815	.835	1.032	1.051
6103R	85248	1"	200'	200'	96	1.032	1.055	1.287	1.315
6104R	85249	1-1/4"	200'	200'	192	1.370	1.394	1.630	1.661
6105R	85250	1-1/2"	100'	100'	79	1.579	1.598	1.866	1.902
6105R150	85527	1-1/2"	150'	150'	120	1.579	1.598	1.866	1.902
6106R	85251	2"	100'	100'	96	2.020	2.043	2.339	2.374