



CAT#	A	B	C	D
820	1.00	.3125	.6875	.125
821	1.1875	.375	.75	.1875
822	1.3125	.50	.8125	.25
823	1.5313	.50	1.00	.25
824	1.9688	.625	1.375	.25
825	2.1875	.75	1.5625	.375
826	2.625	1.00	2.00	.3125
827	3.1875	1.00	2.625	.375
828	4.25	1.50	2.75	.375
829	4.625	2.00	3.6875	.50



CAT#	A	B	C	D
814	3.375	1.50	2.00	.375
815	3.625	2.75	2.75	.375
816	4.4375	2.00	2.5625	.500



SOLDERLESS LUGS

COPPER

TOPAZ CAT #	UPC#	AMP RATING	RECOMMENDED TORQUE IN LBS	WIRE RANGE MIN-MAX	BOLT SIZE	SHIP WT/ CASE	WT/ CASE
----------------	------	---------------	------------------------------	-----------------------	--------------	---------------------	-------------

SINGLE HOLE

• OFFSET TANG

820	18270	25	20	14-10	1/8	250	3
821	18280	35-50	45	14-6	3/16	250	6
822	18290	70	50	14-4	1/4	200	6
823	18300	70-90	50	12-2	1/4	200	9
824	18310	125	50	8-1/0	1/4	100	11
825	18320	175	124	4-3/0	3/8	25	3
826	18330	225	204	6-4/0	5/16	25	6
827	18340	300	325	1/0-350 MCM	3/8	20	10
828	18350	400	375	4/0-500 MCM	3/8	10	7
829	18360	650	500	600MCM-1000 MCM	1/2	4	7



DUPLEX TERMINAL LUGS

814	18240	400	—	2#1/0-2#4/0	3/8	10	5
815	18250	600	—	2#1/0-2#350 MCM	3/8	5	5
816	18260	800	—	2#4/0-2#500 MCM	1/2	4	6

GROUNDING BRIDGE

COPPER

INTERSYSTEM BONDING BRIDGE

Meets requirements of 2008 NEC Article 250.49

TOPAZ CAT #	UPC#	WIRE RANGE MIN-MAX	UNIT CTN	SHIP WT/ CASE	WT/ CASE
813	17544	6-2 AWG	1	10	6

[DOWNLOAD SPEC SHEET](#)

