

Rigid Conduit Bodies

Threaded T Type

Features

- Threaded T type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast

Standard Finish

- Powder coat



UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Max. Number	Wire Size	Unit Carton	Ship Case	Weight/Case	Inches		
				Max. Size				A	B	C
T1	21730	1/2"	1	6 AWG	10	100	32	4.72	1.37	2.03
T2	21740	3/4"	2	6 AWG	10	50	26	5.57	1.625	2.335
T3	21750	1"	3	6 AWG	5	25	18	6.46	1.90	2.705
T4	21760	1-1/4"	3	2 AWG	2	10	17	8.528	2.77	3.63
T5	21770	1-1/2"	3	2 AWG	2	10	19	8.528	2.77	3.63
T6	21780	2"	3	2/0 AWG	---	5	7	10.831	3.335	3.98
T7	21790	2-1/2"	3	4/0 AWG	---	1	7	13.50	4.06	5.825
T8	21800	3"	3	250 MCM	---	1	7	13	4.685	5.825
T9	21810	3-1/2"	3	350 MCM	---	1	9	15.937	5.45	7.06
T10	21820	4"	4	350 MCM	---	1	9	15.937	5.45	7.06