

**Product**

**PS-II Adapter Assembly (Male NPT)**

**Project Information**

|             |                     |
|-------------|---------------------|
| Job Name:   | Date Submitted:     |
| Location:   | Submitted By:       |
| Engineer:   | Approved By:        |
| Contractor: | Manufacturer's Rep: |

**Installation**

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

**Application Information**

Connection of PS-II to NPT fitting.



**Technical Data**

Materials

|                                      |                 |
|--------------------------------------|-----------------|
| Nut, Adapter, Flange and Split Rings | Yellow Brass    |
| Insert and 1" Split Ring             | Stainless Steel |

Pressure Ratings (used with tubing)

|                                  |         |
|----------------------------------|---------|
| Specification Operating Pressure | 25 PSIG |
| Max Test Pressure                | 40 PSIG |

Temperature Ratings (used with tubing)

|                             |                  |
|-----------------------------|------------------|
| Operating Temperature Range | -20 to 200 Deg F |
|-----------------------------|------------------|

**Codes**

ICC Codes (IFGC, IRC, IMC, IPC), NFPA 54 , UPC, CAN/CSA B149.1, NFPA 58

**Standards**

ANSI LC1 / CSA 6.26, ANSI Z223.1

**Listings**

CSA, ICC PMG 1046 / 1052, IAPMO (UPC) File No. 4665

**Dimensional Information**

| ✓                        | Size   | P/N          | Diameter across flats (Nom. in.) | Fitting length (Nom. in.) | TracPipe or CounterStrike Size | Weight (lbs) |
|--------------------------|--------|--------------|----------------------------------|---------------------------|--------------------------------|--------------|
| <input type="checkbox"/> | 3/8"   | FGP-UGF-375  | 1"                               | 3-3/4"                    | 3/8"                           | 0.45         |
| <input type="checkbox"/> | 1/2"   | FGP-UGF-500  | 1-1/8"                           | 3-7/8"                    | 1/2"                           | 0.50         |
| <input type="checkbox"/> | 3/4"   | FGP-UGF-750  | 1-3/8"                           | 4-1/8"                    | 3/4"                           | 0.65         |
| <input type="checkbox"/> | 1"     | FGP-UGF-1000 | 1-5/8"                           | 4-3/4"                    | 1"                             | 0.90         |
| <input type="checkbox"/> | 1-1/4" | FGP-UGF-1250 | 2-5/8"                           | 5-1/4"                    | 1-1/4"                         | 1.60         |
| <input type="checkbox"/> | 1-1/2" | FGP-UGF-1500 | 3"                               | 5-7/8"                    | 1-1/2"                         | 2.65         |
| <input type="checkbox"/> | 2"     | FGP-UGF-2000 | 3-1/16"                          | 6-1/2"                    | 2"                             | 4.30         |