TRACPipe® TRACPipe® AP TRACPipe® PS II

Product

Threaded Coupling with Flip Sleeve Assembly for TracPipe and TracPipe AP Sizes 3/8" - 1"

Project Information

Job Name:	Date Submitted:
Location:	Submitted By:
Engineer:	Approved By:
Contractor:	Manufacturer's Rep:

Installation

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

Application Information

Coupling fitting between TracPipe or TracPipe AP Tubing. For use indoor, outdoor, and concealed location applications.



Technical Data

Materials

Nut and Body	Yellow Brass
3/8" - 3/4" Split Rings	Bronze/Brass
1" Split Rings	Stainless Steel
Sleeve Adapter	HDPE
Flip Sleeve	Silicone

Pressure Ratings (used with tubing)

Specification Operating Pressure	25 PSIG
CSA International Evaluation Report - Max Operating Pressure, 3/8" through 1"	125 PSIG

Temperature Ratings (used with tubing)

Operating Temperature Range	-20 to 200 Deg F

Codes

ICC Codes (IFGC, IRC, IMC), NFPA 54 / ANSI Z223.1, UPC, CAN/CSA B149.1, NFPA 58

Standards

ANSI LC1 / CSA 6.26, ANSI Z223.1

Listings

CSA, ICC PMG 1058, IAPMO (UPC) File No. 3682

Dimensional Information

✓	Size	P/N	Diameter Silicone Sleeve (Nom. in.)	Diameter across flats (Nom. in.)	Fitting length w/Flip Sleeve Tucked (Nom. in.)	TracPipe or TracPipe AP Size		Weight (lbs)
❒	3/8"	FGP-AF-CPLG-375	1-3/8"	1-1/8"	4 3/8"	3/8"	3/8"	0.60
❒	1/2"	FGP-AF-CPLG-500	1-9/16"	1-1/4"	4 3/8"	1/2"	1/2"	0.70
❒	3/4"	FGP-AF-CPLG-750	1-13/16"	1-1/2"	4 5/8"	3/4"	3/4"	0.95
❒	1"	FGP-AF-CPLG-1000	2-3/16"	1-3/4"	4 7/8"	1"	1"	1.20

Omega Flex, Inc. * 451 Creamery Way * Exton, PA 19341
Tel: 610-524-7272 * Toll Free: 800-671-8622 * Fax: 610-524-7282
www.omegaflex.com

© 2026 Omega Flex, Inc.
TracPipe is a registered trademark of Omega Flex, Inc.