TRACPipe® TRACPipe® AP TRACPipe® PS II

Product

90° Steel Flange Fitting (Male-NPT) with Flip Sleeve Assembly for TracPipe or TracPipe AP Size 1/2"

Project Information


Job Name:	Date Submitted:
Location:	Submitted By:
Engineer:	Approved By:
Contractor:	Manufacturer's Rep:

Installation

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

Application Information

Termination fitting between TracPipe or TracPipe AP Tubing and NPT thread. Fitting thread is Male NPT. For use indoor, outdoor, and concealed location applications.



Technical Data

Materials

Nut and Adapter	Yellow Brass
1/2" Split Rings	Bronze/Brass
Sleeve Adapter	HDPE
Flip Sleeve	Silicone
Mounting Flange	E- Coated GA Steel

Pressure Ratings (used with tubing)

Specification Operating Pressure	25 PSIG
CSA International Evaluation Report - Max Operating Pressure, 1/2"	125 PSIG

Temperature Ratings (used with tubing)

Operating Temperature Range	-20 to 200 Deg F

Codes

ICC Codes (IFGC, IRC, IMC), NFPA 54 / ANSI Z223.1, UPC, CAN/CSA B149.1, NFPA 58

Standards

ANSI LC1 / CSA 6.26, ANSI Z223.1

Listings

CSA, ICC PMG 1058, IAPMO (UPC) File No. 3682

Dimensional Information

✓	*Size*	*P/N*	*Diameter Sleeve Adapter (Nom. in.)*	*Diameter across flats (Nom. in.)*	*Fitting length w/Flip Sleeve Tucked (Nom. in.)*	*Plate Size I X W (in.)*	*Male NPT Pipe Size*	*Weight (lbs)*
❒	1/2"	FGP-AF-E-500	1-9/16"	1-1/4"	3-1/16"	4-1/4" - 2-3/4"	1/2"	1.05

© 2026 Omega Flex, Inc.
TracPipe is a registered trademark of Omega Flex, Inc.