TRACPipe® TRACPipe® AP TRACPipe® PS II

Product

Metal Wall Box with 90° Valve with Floppy Conduit Adapter Assembly for TracPipe and TracPipe AP Sizes 3/8" - 3/4"

Project Information

Job Name:	Date Submitted:
Location:	Submitted By:
Engineer:	Approved By:
Contractor:	Manufacturer's Rep:

Installation

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

Application Information

Metal wall box with valve for use with zero clearance appliance installations. Reverse Mounting tabs to accommodate double sheetrock walls. For Indoor Use Only. Wall Box is Fire Rated to UL 1479. Includes Floppy conduit and adapter for protection.

Technical Data

Materials

Nut and Body	Yellow Brass
3/8" - 3/4" Split Rings	Bronze/Brass
Metal Wall Box	Powder Coated Steel
Floppy Conduit Adapter	Zinc-Plated Steel
Floppy Conduit	GA Steel
Valve	Brass Alloy - Nickel Plated

Pressure Ratings (used with tubing)

Specification Operating Pressure	25 PSIG
CSA International Evaluation Report - Max Operating Pressure, 3/8" through 3/4"	125 PSIG

Temperature Ratings (used with tubing)

Operating Temperature Range	-20 to 200 Deg F



Codes

ICC Codes (IFGC, IRC, IMC), NFPA 54 / ANSI Z223.1, UPC, CAN/CSA B149.1, NFPA 58

Standards

ANSI LC1 / CSA 6.26, ANSI Z223.1

Listings

CSA, ICC PMG 1058, IAPMO (UPC) File No. 3682

Dimensional Information

✓	TP Size	P/N	Diameter Floppy Conduit Adapter (Nom. in.)	Diameter across flats (Nom. in.) Nut	Diameter across flats (Nom. in.) Valve Body	Fitting Height (Nom. in.)	Box Dimensions L X W X D (in.)	Valve NPT Pipe Size	Weight (lbs)
❒	3/8"	FGP-AF-WB-375	1-3/8"	1-1/8"	1-1/16"	2-3/4"	5" X 6-7/8" X 3-3/4"	1/2"	3.1
❒	1/2"	FGP-AF-WB-500	1-9/16"	1-1/4"	1-1/16"	2-3/4"	5" X 6-7/8" X 3-3/4"	1/2"	3.1
❒	3/4"	FGP-AF-WB-750	1-13/16"	1-1/2"	1-5/16"	2-3/4"	5" X 6-7/8" X 3-3/4"	3/4"	3.6

Omega Flex, Inc. * 451 Creamery Way * Exton, PA 19341
Tel: 610-524-7272 * Toll Free: 800-671-8622 * Fax: 610-524-7282
www.omegaflex.com

© 2026 Omega Flex, Inc.
TracPipe is a registered trademark of Omega Flex, Inc.