TRACPipe® TRACPipe® AP TRACPipe® PS II

Product

Threaded Coupling for TracPipe PS-II Sizes 3/8" - 1"

Project Information

Job Name:	Date Submitted:
Location:	Submitted By:
Engineer:	Approved By:
Contractor:	Manufacturer's Rep:

Installation

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

Application Information

Coupling fitting between TracPipe PS-II Tubing. For use indoor, outdoor, and underground applications.



Technical Data

Materials

Front Pipe, Flange Body, and Rear Flange	Yellow Brass
Spiral Retaining Ring, Pusher, and 1" Split Rings	Stainless Steel
3/8"- 3/4" Split Rings	Bronze/Brass
Rear Flange	Acetal
Front Pipe O-Ring and Rear Seal	BUNA-N

Pressure Ratings (used with tubing)

Specification Operating Pressure	25 PSIG
CSA International Evaluation Report - Max Operating Pressure, 3/8" through 1"	125 PSIG

Temperature Ratings (used with tubing)

Operating Temperature Range	-20 to 200 Deg F

Codes

ICC Codes (IFGC, IRC, IMC), NFPA 54 / ANSI Z223.1, UPC, CAN/CSA B149.1, NFPA 58

Standards

ANSI LC1 / CSA 6.26, ANSI Z223.1

Listings

CSA, ICC PMG 1058 / 1052, IAPMO (UPC) File No. 4665

Dimensional Information

✓	*Size*	*P/N*	*Diameter Rear Flange (Nom. in.)*	*Diameter across flats (Nom. in.)*	*Fitting length (Nom. in.)*	*TracPipe PS-II Size*		*Weight (lbs)*
❒	3/8"	FGP-UGC2-375	1-11/16"	1-3/8"	5-5/8"	3/8"	3/8"	1.55
❒	1/2"	FGP-UGC2-500	2"	1-5/8"	5-7/8"	1/2"	1/2"	2.1
❒	3/4"	FGP-UGC2-750	2-1/4"	1-7/8"	6"	3/4"	3/4"	2.5
❒	1"	FGP-UGC2-1000	2-1/2"	2-1/8"	6-1/2"	1"	1"	3.30

Omega Flex, Inc. * 451 Creamery Way * Exton, PA 19341
Tel: 610-524-7272 * Toll Free: 800-671-8622 * Fax: 610-524-7282
www.omegaflex.com

© 2026 Omega Flex, Inc.
TracPipe is a registered trademark of Omega Flex, Inc.