TRACPipe® TRACPipe® AP TRACPipe® PS II

**Product**

## 4-Bolt Straight Fitting (Male-NPT) Assembly for TracPipe PS-II Sizes 1-1/4" - 2"

**Project Information**

| | |
|---|---|
| Job Name: | Date Submitted: |
| Location: | Submitted By: |
| Engineer: | Approved By: |
| Contractor: | Manufacturer's Rep: |

**Installation**

Must be installed in accordance with the TracPipe Design Guide and Installation Instructions and all applicable codes

**Application Information**

Transition fitting between TracPipe PS-II Tubing and NPT thread. Fitting thread is Male NPT. For use indoor, outdoor, and underground applications.



**Technical Data**

Materials

| | |
|---|---|
| Front Pipe, Flange Body, Rear Flange | Yellow Brass |
| Retaining Ring, and Split Ring | Stainless Steel |
| Rear Seal and Front Pipe O-Ring | BUNA-N |
| 5/16-18 Threaded HEX Bolt (3" Long) | Stainless Steel |

Pressure Ratings (used with tubing)

| | |
|---|---|
| Specification Operating Pressure | 25 PSIG |
| CSA International Evaluation Report - Max Operating Pressure, 1-1/4"only | 125 PSIG |

Temperature Ratings (used with tubing)

| | |
|---|---|
| Operating Temperature Range | -20 to 200 Deg F |

**Codes**

ICC Codes (IFGC, IRC, IMC), NFPA 54, UPC, CAN/CSA B149.1, NFPA 58

**Standards**

ANSI LC1 / CSA 6.26, ANSI Z223.1

**Listings**

CSA, ICC PMG 1058 / 1052, IAPMO (UPC) File No. 4665

**Dimensional Information**

| ✓ | *Size* | *P/N* | *Circular Nut Diameter (Nom. in.)* | *Diameter across flats (Nom. in.)* | *Fitting length (Nom. in.)* | *TracPipe PS-II Size* | *Male NPT Pipe Size* | *Weight (lbs)* |
|---|---|---|---|---|---|---|---|---|
| ❒ | 1-1/4" | FGP-UGF2-1250 | 3-3/8" | 3" | 4-5/16" | 1-1/4" | 1-1/4" | 3.15 |
| ❒ | 1-1/2" | FGP-UGF2-1500 | 3-3/4" | 3-3/4" | 4-9/16" | 1-1/2" | 1-1/2" | 6.60 |
| ❒ | 2" | FGP-UGF2-2000 | 4-3/8" | 4" | 4-11/16" | 2" | 2" | 8.30 |

Omega Flex, Inc. * 451 Creamery Way * Exton, PA 19341
Tel: 610-524-7272 * Toll Free: 800-671-8622 * Fax: 610-524-7282
www.omegaflex.com



© 2026 Omega Flex, Inc.

*TracPipe is a registered trademark of Omega Flex, Inc.*